

# CONSHOCKEN STEEL PRODUCTS, INC.

---

## HOOK LIFT STYLE CONTAINER LIGHT DUTY SPECIFICATIONS

FLOOR: 10 GAUGE STEEL PLATE

CROSSMEMBERS: 3" HIGH STRENGTH STRUCTURAL STEEL CHANNEL 20" SPACING

SIDE RAILS: 3" HIGH STRENGTH STRUCTURAL STEEL CHANNEL

GUSSETS: 3/16" PLATE AT EVERY OTHER CROSSMEMBER WELDED SOLID

MAIN RAILS: 6" X 2" X 3/16" STRUCTURAL STEEL TUBE

REAR WHEELS: 8" X 10" HEAVY DUTY STEEL PIPE

TOP RAILS: 3" X 4" X 11 GAUGE STRUCTURAL STEEL TUBE

SIDES: 12 GAUGE STEEL PLATE FULLY WELDED TO TOP RAIL AND FLOOR PLATE

SIDE POSTS: 12 GAUGE STEEL PLATES FORMED 3" DEEP X 5" WIDE-40" SPACING

TIE DOWN BARS: 5/8" SOLID STEEL ROUND BAR

BULKHEAD: 12 GAUGE STEEL PLATE FULLY WELDED TO TOP RAIL AND FLOOR PLATE

**TAILGATE:** 12 GAUGE STEEL PLATE WITH 10 GAUGE BOTTOM GATE PLATE

STABILIZER PLATE: 3/16" PLATE. 1 ON HINGE SIDE

HINGES AND SUPPORTS: 1/2" PLATES 8" X 3"; 8" X 7" W/ REMOVABLE 1" GREASABLE PIN

LATCHES: 3/4" X 4" STEEL PLATE, VERTICAL – LIFT TYPE SYSTEM


TAILGATE ALIGNER: 3/4" STEEL PLATE (2)

HOOK MANUFACTURED TO CUSTOMER DRAWING

**FORMED HOOK SUPPORT:** INSIDE CONTAINER ON BULKHEAD BEHIND HOOK

ALL CONTAINERS FULLY COATED WITH 2 COATS OF HEAVY DUTY RUST INHIBITIVE PRIMER

ALL CONTAINERS FINISHED WITH 3 COATS OF HEAVY DUTY CONTAINER ENAMEL



301 RANDOLPH AVENUE  
AMBLER, PA 19002  
(215) 283-9222  
(215) 289-1198 (F)